



**13.5oz LAMINATED VINYL**

**MATERIAL DESCRIPTION**

<b>Basic Fabric</b>	<b>9x9 Polyester Weft</b>	<b>DIN 60001</b>
<b>Denier</b>	<b>1,000 x 1,000</b>	
<b>Weight</b>	<b>13.5 OZ/YD<sup>2</sup></b>	<b>FS-191-5400</b>
<b>Finish</b>	<b>Matte</b>	
<b>Thickness</b>	<b>.42mm</b>	<b>FS-191-5401</b>
<b>Tensile Strength</b>	<b>240 lb x 240 lb (Grab)</b>	<b>FS-191-5102</b>
<b>Tear Strength</b>	<b>75 lb x 75 lb (Tongue)</b>	<b>FS-191-5134</b>
<b>Adhesion</b>	<b>12 x 12 lbs/inch</b>	<b>FS-101-5970</b>
<b>Elongation</b>	<b>20/19%</b>	<b>FS-191-5102</b>
<b>Flame Resistance (1)</b>	<b>California Fire Marshall</b>	<b>Reg.#: FA-41501</b>
<b>Flame Resistance (2)</b>	<b>NFPA-701 (Pass)</b>	
<b>Cold Crack</b>	<b>-20° F</b>	<b>FS-191-5874</b>
<b>Roll Width</b>	<b>61"</b>	
<b>Roll Length</b>	<b>100 Yard</b>	

*\* Results above reflect typical performance characteristics of the product listed. This document should not be used as certification to any specification.*

