



**40 MIL CLEAR PVC**

**MATERIAL DESCRIPTION**

<b>Roll Thickness</b>	<b>40 Mil</b>	
<b>Roll Width</b>	<b>48"</b>	
<b>Finish</b>	<b>Double Polished</b>	
<b>Color</b>	<b>Clear</b>	
<b>Hardness (15 sec. delay)</b>	<b>80 A Scale</b>	<b>ASTM-D-2240</b>
<b>Tensile Strength</b>	<b>2700 PSI</b>	<b>ASTM-D-412</b>
<b>Ultimate Elongation</b>	<b>350%</b>	<b>ASTM-D-412</b>
<b>Graves Tear</b>	<b>275</b>	<b>ASTM-D-1004</b>
<b>100% Modulus</b>	<b>1250 PSI</b>	<b>ASTM-D-412</b>
<b>Brittleness Temperature</b>	<b>-37° F</b>	<b>ASTM-D-746</b>
<b>Operating Temperature</b>	<b>0°F to 150°F</b>	
<b>UV Resistance</b>	<b>Yes</b>	
<b>Flammability Rating</b>	<b>Select Material Compliant with CA State Fire Marshall</b>	

*\* Results above reflect typical performance characteristics of the product listed. This document should not be used as certification to any specification.*

