



## Neoprene Coated Fiberglass

### MATERIAL DESCRIPTION

<b>Fabric Weight</b>	<b>24 OZ/YD<sup>2</sup> or 30 OZ/YD<sup>2</sup></b>
<b>Roll Width</b>	<b>40", 60", &amp; 72"</b>
<b>Nominal Thickness</b>	<b>0.065"</b>
<b>Fabric Finish</b>	<b>Compounded neoprene rubber or acrylic rubber used on one side of the cloth and the other side dyed a light yellow.</b>
<b>Service Temperature</b>	<b>Coating: 225°F Cloth: 1000°F</b>
<b>Base Fabric Content</b>	<b>100% Fiberglass Yarns</b>
<b>Weave</b>	<b>Twill</b>
<b>Count</b>	<b>Warp: 17 Fill: 15</b>
<b>Color</b>	<b>Yellow</b>
<b>Application</b>	<b>Used to ease fabrication and increase abrasion resistance. Used for safety apparel, welding blankets, curtains and shields.</b>

**Other: Material should be tested for its suitability in any application. Users should also familiarize themselves with the MSDS before handling. Neoprene coated fiberglass products must be used in a well ventilated area.**

*\* Results above reflect typical performance characteristics of the product listed. This document should not be used as certification to any specification.*