

Industrial Curtain Wall - 14 oz

14 oz Vinyl Industrial Curtain Walls are supplied with one color below the see-through window, and another above the see-through window. Kits can include track, rollers, mounting, and end stops.

Colors Available: White, Black, Blue, Gray, Red, Yellow, Green, and Brown

| \bigcirc | Part - IC 14oz X XX | | | | |
|---|--|---------------------------------|----------------------------------|---|---------------|
| | 14 oz Laminate Vinyl | Clear PVC Window | Hem Chain | Velcro | Thread |
| Material | Bi-Axial Weft Polyester Scrim Laminated Over PVC | Double Polished Clear PVC | Zinc Plated Steel | Woven Nylon | Nylon |
| Weight | 13.5 oz sq/yd | 18 oz sq/yd | .25 lb/ft | 6140 yds/lb | .019 oz/sq in |
| Thickness | 15 Mils | 20 Mils | 1/2" | .013" | .010" |
| Tensile Strength | 220 lbs/sq in | 210 lbs/ sq in | N/A | N/A | N/A |
| Temperature Limits | -10 to +180 F | -20 to +180 F | N/A | -20 to +3,212 F | -20 to +445 F |
| Flammability California Sta Fire Marshall | te Pass | Pass | N/A | | N/A |
| NFPA-701 | Pass | Pass | N/A | Pass | N/A |
| Mildew & Rot Resistance | Mildew Inhibitor | Excellent | N/A | Good | Good |
| Acid Resistan | ce Good | Good | Excellent | Good | Good |
| UV Resistance | e UV Inhibitor | UV Inhibitor | N/A Document Should Not Be Us | Good sed as A Certification to Any S | Good |