

Laser Curtains - B-35, 3-Layer

Laser Safety Curtains with B-35 three layer material are manufactured with sewn nylon thread, stainless steel or black grommets and optional chain as well as valance panels. Laser Barrier Curtain Kits can include track, rollers, mounting, and end stops.

\bigcirc	Part - LC 3L XX			\bigcirc
	B-35 Laser Material, 3-Layer	Hem Chain	Velcro	Thread
Material	52% Polyester; 48 Cotton with Proprietary Coating	Zinc Plated Steel	Woven Nylon	Nylon
Weight	33.75 oz sq/yd 3.75 oz sq/ft	.25 lb/ft	6140 yds/lb	.019 oz/sq in
Color	Black	Silver (Hidden)	Black	Black
Maintenance Strength	Dry Cleanable	N/A	N/A	N/A
Temperature Limits	-10 to +140 F	N/A	-20 to +3,212 F	-20 to +445 F
Flammability California State Fire Marshall	Pass	N/A		N/A
NFPA-701	Pass	N/A	Pass	N/A
Irradiance Resistance	300 W / Cm2	N/A	N/A	N/A
Laser Certification	ANSI Z136.8-2012	N/A	N/A	N/A
* Results Above Re	flect Typical Chararistics of the Product Listed. This D	ocument Should Not Be Us	ed as A Certification to Any S	

Results Above Reflect Typical Chararistics of the Product Listed. This Document Should Not Be Used as A Certification to Any Specification.

(800) 347-8368 (812) 234-4586 (812) www.SteelGuardSafety.com