





Sound Shield™ Noise Control Curtains Block & Attenuate Noise Levels in Extreme Industrial Environments with the Highest STC Level on the Market and Custom Designed Solutions to Your Needs.

Benefits:

- Custom Made by Material & Size per Application
- Noise Reduction up to 47 Db
- Improves Focus & Working Conditions
- Prevents OSHA Fines for Noise Over 85 Db
- 3 Styles to Choose –Fold-A-Way, Screen Frame, or Stationary
- Economical Alternative to Metal Sound Enclosures

Sound Shield Fold-A-Way Features:

- Panels Collapse & Fold a Way in Fan Pattern
- Mass Loaded Vinyl w/ Viscoelastic Dampener Encased Around 18 oz Coated Vinyl Material
- · Resistant to Oil, Water, & Most Chemicals
- Rated for STC 30
- Panels Attach Modularly with 2"Velcro
- Moveable Track System Allows Easy Access & Storage

Sound Shield SCC Features:

- 1, 2, or 3 Layer Panels to Choose From
- · Features Quilted Fiberglass and/or Mass Loaded Vinyl Layers
- Fiberglass is Excellent for Absorption as well as Sound Reflection
- · Resistant to Oil, Water, & Most Chemicals
- Rated for STC 30
- Panels Attach Modularly with 2"Velcro



Sound Shield Fold-A-Ways Unique Fan Fold Allows for Easy Storage of Curtains



Use As a Warehouse Divider to Block Sound as Well as Dust & Contaminants

Block Sound In These Applications:

- HVAC
- Compactors
- Blowers
- Construction Noise
- Compressors
- Stamping Presses
- Large machinery
- · Any Large machinery
- Grinders

Width x Height	Part Number w/Track Hardware	Part Number Curtain Only

MODEL SCC-8

One-Layer of Fiberglass Batting with One-Side Quilted Vinyl Cover on the Front, Back is Unfinished. Grommets 1' O.C on Top -2' O.C. on Sides

4' × 4'	_	SCC AB 4.5x4
4' × 6'	_	SCC AB 4.5x6
4' × 8'	_	SCC AB 4.5x8
4' × 10'	_	SCC AB 4 5x10

MODEL SCC-9

Two-Layers of Fiberglass Batting with a Two-Sided Quilted Vinyl Cover on Front and Back. Grommets 1' 0.C on Top - 2' 0.C. on Sides

4' × 4'	_	SCC DB 4.5x4
4' × 6'	_	SCC DB 4.5x6
4' × 8'	_	SCC DB 4.5x8
4' × 10'	_	SCC DB 4.5x10
BULK ROLLS		
4' × 50'	_	FAs NS FIBER
4' x 25'	_	FAs NS MASS

MODEL SCC-10

Two-Layers of Fiberglass Batting with Two-Sided Quilted Vinyl Cover, Front and Back, Plus One Layer of Mass Loaded Vinyl on the Inside (5 Layers). Grommets 1' O.C on Top — Sides Finished with 2" Velcro

MODEL SAS PORTABLE SCREENS		
4' x 12'	SCCT 4.5x12	SCC NT 4.5x12
4 ′ × 11′	SCCT 4.5x11	SCC NT 4.5x11
4 ′× 10′	SCCT 4.5x10	SCC NT 4.5x10
4' × 9'	SCCT 4.5x09	SCC NT 4.5x09
4' × 8'	SCCT 4.5x08	SCC NT 4.5x08
4' × 7'	SCC I 4.5x07	SCC NT 4.5x07

4'x 8' 1-Single	SAS 4.5x8 1S	_
4'x 8' 2-Sided	SAS 4.5x8 2S	_
4'x 8' 3-Sided	SAS 4.5x8 3S	_
4' x 8' 4-Sided	SAS 4.5x8 4S	_

MODEL FOLD-A-WAY

1.6 lbs per Sq/Ft Mass Loaded Vynyl with iscelatic coating surrounded by 2-layers of 18oz coated vinyl - grommets 1'o.c.on top -sides finished with 2' velcro

5' x 8'	SSF 8x5	
9'-11" x 8'	SSF 8x10	
5' x 9'	SSF 9x5	
9'-11" x 9'	SSF 9x10	
5' x 10'	SSF 10x5	
9′-11″ x 10′	SSF 10x10	

Model SCC-10 Track Mounted



Model SAS Portable Screens



Sound Shield™ Effectiveness

